

List Price \$119.00 USD

Availability **Stock Item: This item is normally stocked in our distribution facility.****Technical Characteristics**

| | |
|-----------------------------|-----------------------------------------------------------------------------------------------------------------|
| Certifications | UL Listed (E164862 / NLDX) - CSA Certified (LR43364 3211 04) - IEC Rated (60647-4) - CE Marked - RoHS Compliant |
| Contacteur Type | Non-Reversing |
| Inductive Amperes (AC3) | 9A |
| Resistive Amperes (AC1) | 20A |
| Horsepower Rating (1-Phase) | 0.5HP@115Vac - 1HP@230Vac |
| Horsepower Rating (3-Phase) | 2HP@200/230Vac - 5HP@460Vac - 7.5HP@575Vac |
| Marketing Trade Name | TeSys |
| Maximum Voltage Rating | 600 Vac |
| Mounting Style | 35mm DIN Rail |
| Number of Poles | 3-Pole (3 NO) |
| Coil Voltage Code | BD |
| Coil Consumption Sealed | 5.4 W |
| Coil Voltage | 24Vdc |
| Coil Consumption Inrush | 5.4 W |
| Weight | 0.71 lbs (0.32 kg) |
| Power Wire Size | #10 to #18 AWG |
| Control Terminal Torque | 15 lb-in (1.7 Nm) |
| Power Terminal Torque | 15 lb-in (1.7 Nm) |
| Terminal Type | Screw Clamp |
| Control Wire Size | #10 to #18 AWG |
| Type | TeSys D |

Shipping and Ordering

| | |
|-------------------|-------------------------------------------------------------------------|
| Category | 22345 - |
| Discount Schedule | I12 |
| GTIN | 00785901213369 |
| Package Quantity | 1 |
| Weight | 1.17 lbs. |
| Availability Code | Stock Item: This item is normally stocked in our distribution facility. |
| Returnability | Y |
| Country of Origin | FR |

As standards, specifications, and designs change from time to time, please ask for confirmation of the information given in this document.