3RT1054-6AP36 Page 1

SIEMENS

Product data sheet 3RT1054-6AP36



CONTACTOR, 55KW/400V/AC-3, AC(40...60HZ)/DC OPERATION UC 220...240V AUX. CONTACTS 2NO+2NC, 3-POLE, SIZE S6 BAR CONNECTIONS CONVENTIONAL


OPERATING MECHAN. SCREW TERMINAL

General details:	
Size of the contactor	S6
Number of poles	3
Control circuit:	
Design of activation of the operating mechanism	conventional
Type of voltage	AC/DC
Control supply voltage	
at 50 Hz / for AC / rated value / minimum	220 V
• at 50 Hz / for AC / rated value / maximum	240 V
at 60 Hz / for AC / rated value / minimum	220 V
at 60 Hz / for AC / rated value / maximum	240 V
for DC / rated value / minimum	220 V
• for DC / rated value / maximum	240 V
Supply voltage frequency / for auxiliary and control current circuit / rated value	
• minimum	50 Hz
• maximum	60 Hz
Design of the surge suppressor	with varistor
Main circuit:	

3RT1054-6AP36 Page 2

Number of NC contacts / for main contacts	0
Number of NO contacts / for main contacts	3
Operating current	
• at AC-3 / at 400 V / rated value	115 A
• at AC-1 / at 400 V / rated value	160 A
Service power	
• at AC-3 / at 400 V / rated value	55 kW
• at AC-1 / at 400 V / rated value	92 kW
Auxiliary circuit:	
Identification number and letter for switching elements	22
Number of NO contacts / for auxiliary contact	2
Number of NC contacts / for auxiliary contact	2
Connection type:	
Design of the electrical connection / for main current circuit	screw-type terminals
Design of the electrical connection / for auxiliary and control current circuit	screw-type terminals
Mounting/fixing:	
Type of fixing/fixation	screw fixing
Series installation	Yes

3RT1054-6AP36 Page 3



last change: 10/31/2006

Technical Assistance:	Telephone:	+49 (0) 911-895-5900 (8°° - 17°° CET)	
	Fax:	+49 (0) 911-895-5907	
	E-Mail:	technical-assistance@siemens.com	
	Internet:	www.siemens.de/lowvoltage/technical-assistance	