SIEMENS

Product data sheet

3RT1056-6AP36

CONTACTOR, 90KW/400V/AC-3, AC(40...60HZ)/DC OPERATION UC 220...240V AUXIL. CONTACTS 2NO+2NC 3-POLE, SIZE S6 BAR CONNECTIONS CONVENT. OPERATING MECHANISM SCREW TERMINAL

Size of the contactor	S6
Number of poles	3
Control circuit:	
Design of activation of the operating mechanism	conventional
Type of voltage	AC/DC
Control supply voltage	
 at 50 Hz / for AC / rated value / minimum 	220 V
 at 50 Hz / for AC / rated value / maximum 	240 V
 at 60 Hz / for AC / rated value / minimum 	220 V
 at 60 Hz / for AC / rated value / maximum 	240 V
 for DC / rated value / minimum 	220 V
 for DC / rated value / maximum 	240 V
Supply voltage frequency / for auxiliary and control current circuit / rated value	
• minimum	50 Hz
• maximum	60 Hz
Design of the surge suppressor	with varistor
Main circuit:	



Number of NC contacts / for main contacts	0
Number of NO contacts / for main contacts	3
Operating current	
 at AC-3 / at 400 V / rated value 	185 A
 at AC-1 / at 400 V / rated value 	215 A
Service power	
 at AC-3 / at 400 V / rated value 	90 kW
 at AC-1 / at 400 V / rated value 	121 kW
Auxiliary circuit:	
Identification number and letter for switching elements	22
Number of NO contacts / for auxiliary contact	2
Number of NC contacts / for auxiliary contact	2
Connection type:	
Design of the electrical connection / for main current circuit	screw-type terminals
Design of the electrical connection / for auxiliary and control current circuit	screw-type terminals
Mounting/fixing:	
Type of fixing/fixation	screw fixing
Series installation	Yes



last o	change:
--------	---------

10/31/2006

Technical Assistance:	Telephone:	+49 (0) 911-895-5900 (8°° - 17°° CET)
	Fax:	+49 (0) 911-895-5907
	E-Mail:	technical-assistance@siemens.com
	Internet:	www.siemens.de/lowvoltage/technical-assistance